Carriage Bolts (Square Neck Round Head Bolts)

Class 8.8 DIN 603 Plain Finish



| M6 - 1.00 |                |                      |                     |  |
|-----------|----------------|----------------------|---------------------|--|
| Length    | Part<br>Number | Lbs. Per<br>100 Pcs. | Package<br>Quantity |  |
| 25MM      | 2002432        | 1.87                 | 100                 |  |
| 30MM      | 1476085        | 2.12                 | 100                 |  |
| 35MM      | 1476095        | 2.36                 | 100                 |  |
| 40MM      | 1476105        | 2.60                 | 100                 |  |
| 50MM      | 1476125        | 3.09                 | 100                 |  |

| Length | Number  | 100 Pcs. | Quantit |
|--------|---------|----------|---------|
| 25MM   | 1476475 | 5.56     | 50      |
| 40MM   | 2009043 | 7.21     | 50      |
| 45MM   | 2003257 | 7.89     | 50      |
| 70MM   | 2018253 | 11.31    | 25      |
| 80MM   | 2008451 | 12.67    | 100     |
|        |         |          |         |
|        |         |          |         |
|        |         |          |         |

**Part** 

M10 - 1.50

Lbs. Per

Package

| M8 - 1.25 |                |                      |                     |  |
|-----------|----------------|----------------------|---------------------|--|
| Length    | Part<br>Number | Lbs. Per<br>100 Pcs. | Package<br>Quantity |  |
| 25MM      | 2005057        | 3.40                 | 100                 |  |
| 30MM      | 1476285        | 3.75                 | 100                 |  |
| 45MM      | 2017314        | 5.07                 | 50                  |  |
| 80MM      | 2014466        | 8.11                 | 50                  |  |

## Ribbed Neck Carriage Bolts [Ribbed Neck Round Head Bolts]

SAE Grade 5 J429 Zinc Clear

Ribbed neck carriage bolts provide a secure, reliable connection when fastening wood to wood or wood to metal. They are used on conveyor belts associated with the mining industry and on thin plywood in the trailer and truck industries. They have a plain, circular, oval head with a at bearing surface that fastens soft wood without pull-through and a serrated neck to prevent rotation. Their ribbed design grabs the substrate and keeps the bolt from turning when the nut is being tightened by hand or with industrial strength pneumatic tools.

| 1/4 - 20 |                |                      |                     |  |
|----------|----------------|----------------------|---------------------|--|
| Length   | Part<br>Number | Lbs. Per<br>100 Pcs. | Package<br>Quantity |  |
| 3/4"     | 2025287        | 1.57                 | 100                 |  |
| 1"       | 2019178        | 1.83                 | 100                 |  |
| 1 1/4"   | 2025288        | 2.22                 | 100                 |  |

| 5/16 - 18 |                |                      |                     |  |
|-----------|----------------|----------------------|---------------------|--|
| Length    | Part<br>Number | Lbs. Per<br>100 Pcs. | Package<br>Quantity |  |
| 1"        | 2019186        | 3.12                 | 100                 |  |
| 1 1/4"    | 2019187        | 3.62                 | 100                 |  |
| 1 1/2"    | 2011082        | 4.09                 | 50                  |  |
| 2"        | 2019188        | 5.05                 | 50                  |  |
| 2 1/2"    | 2022227        | 6.17                 | 50                  |  |

## Order these parts online!

Click here!

| 3/0 - 10 |                |                      |                     |
|----------|----------------|----------------------|---------------------|
| Length   | Part<br>Number | Lbs. Per<br>100 Pcs. | Package<br>Quantity |
| 1"       | 2019181        | 4.74                 | 50                  |
| 1 1/4"   | 2019182        | 536                  | 50                  |
| 1 1/2"   | 2019183        | 5.93                 | 50                  |
| 2"       | 2019184        | 7.12                 | 50                  |
| 2 1/2"   | 2019185        | 8.35                 | 25                  |
| 3"       | 2025292        | 10.00                | 25                  |



Reference numbers and part weights are provided as a reference only. Actual part weight may vary from weights shown.

1-888-232-1010 fax: (563) 441-6760

 $www. Trinity Hardware HQ. com \\ sales @ Trinity Hardware HQ. com$ 

